

TYRES

Product group	Tyres
Item number	10003301
Valid tyre size	650 / 45 - 22.5
LI / SI / PR	173 A6 / 169 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 331



Notes and features

- The Alliance 331 is perfectly suited to on- and off-road agricultural applications e.g. for tractors, agricultural trailers and similar vehicles
- Its main characteristics are a high load capacity and low inflation pressure
- It replaces conventional tractor tyres or dual constructions because of its high traction, high load capacity and at the same time protects the soil
- Thanks to the permitted speed of 50 km/h, it can also be used on off-road trucks and trailers
- The strong nylon construction and special rubber compound make the tyre very durable

Technical Informations

Item number	10003301
EAN	7291050066938
Valid tyre size	650 / 45 - 22.5
LI / SI / PR	173 A6 / 169 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 331
Carcass properties	HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	139,80
Recommended rim size	20.00DC
Maximum air pressure [bar].	4,50
Section width (mm)	645
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	535
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3567
Contact area [cm²]	1694
Tread depth (mm)	40,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	264.52
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A6	6500	30		4,50	
169 A8	5800	40		4,50	