

TYRES

Product group	Tyres
Item number	10004387
Valid tyre size	VF 710 / 60 R 42 CFO
LI / SI / PR	161 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372



Notes and features

- The Alliance 372 is an IF tyre for high-performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.

Technical Informations

Item number	10004387
EAN	8903635063247
Valid tyre size	VF 710 / 60 R 42 CFO
LI / SI / PR	161 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	261,20
Recommended rim size	25
Permitted rim size	DW25B, DW23B
Maximum air pressure [bar].	1,00
Section width (mm)	710
Outer diameter of tyre [mm].	1923
Stat. radius (SLR) [mm]	849
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5651
Contact area [cm²]	3581.9
Tread depth (mm)	53,6
Number of lugs	20x2
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 D	4625	65		1,00	