

## TYRES

Product group	Tyres
Item number	10004450
Valid tyre size	1050 / 50 R 32
LI / SI / PR	182 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376



## Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.

**Technical Informations**

Item number	10004450
EAN	8903635058809
Valid tyre size	1050 / 50 R 32
LI / SI / PR	182 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	387,30
Recommended rim size	36.00VA
Maximum air pressure [bar].	3,00
Section width (mm)	1050
Outer diameter of tyre [mm].	1870
Stat. radius (SLR) [mm]	806
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5672
Contact area [cm <sup>2</sup> ]	4987
Tread depth (mm)	42,5
Number of lugs	20x2
Tyre capacity 75% [ltr.]	1244.93
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 D	8500	65		3,00	