

TYRES

Product group	Tyres	
Item number	10004672	
Valid tyre size	VF 1050 / 50 R 32 CFO	
LI / SI / PR	198 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 377 + XT	



Technical Informations

Item number	10004672
EAN	8903635059073
Valid tyre size	VF 1050 / 50 R 32 CFO
LI / SI / PR	198 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 377 + XT
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	407,50
Recommended rim size	36.00VA
Maximum air pressure [bar].	3,60
Section width (mm)	1058
Outer diameter of tyre [mm].	1863
Stat. radius (SLR) [mm]	815
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5644
Contact area [cm²]	6068.8
Tread depth (mm)	44,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	1255.05
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
198 D	13200	65		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.