

WHEELS

Product group	Wheels
Item number	10004869
Valid wheel size	340 / 85 R 48
Brand	Alliance
Tread pattern	350
Valid rim size	W 12 x 48
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	298,65
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 10004498
LI / SI / PR	159 A8 / 156 D
Load capacity 1 [kg]	4375
Speed 1 [km/h].	40
Load capacity 2 [kg]	4000
Speed 2 [km/h].	65
Maximum air pressure [bar].	4,60
TL/TT	TL

Tyre colour	Black
E-Ready	No
TRA Code	R1
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	353
Stat. radius (SLR) [mm]	856
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5621
Tread depth (mm)	39,5
Number of lugs	31x2
Tyre capacity 75% [ltr.]	211.2
Assembly Item no. Rim	• 39123170
Load capacity of rim 1 [kg]	4620
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006

Valve seat	External Valve
Disc thickness [mm]	15
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade