

TYRES

Product group	Tyres	
Item number	10165060	
Valid tyre size	165 R 13 C	
LI / SI / PR	94 / 92 R, 8 PR	
TL/TT	TL	
Brand	Onyx	
Tread pattern	NY-W387	





Technical Informations

Item number	10165060
EAN	6953913187921
Valid tyre size	165 R 13 C
LI / SI / PR	94 / 92 R, 8 PR
TL/TT	TL
Brand	Onyx
Tread pattern	NY-W387
M+S	M+S
3PMSF	3PMSF
Rolling resistance	D
Wet grip	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rolling noise [db].	73
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	7,88
Recommended rim size	4.50B
Maximum air pressure [bar].	4,50
Section width (mm)	167
Outer diameter of tyre [mm].	596
Rolling circumference [mm].	1806
Tread depth (mm)	8,8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
94 R	670	170	Single	4,50	
92 R	630	170	Twin	4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.