

TYRES

Product group	Tyres	
Item number	10626366	
Valid tyre size	420 / 85 R 34	
LI / SI / PR	142 D / 139 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Performer 85	



Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



Technical Informations

Item number	10626366
EAN	3286340563512
Valid tyre size	420 / 85 R 34
Alternative size 1	16.9R34
LI / SI / PR	142 D / 139 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	115,50
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	453
Outer diameter of tyre [mm].	1572
Stat. radius (SLR) [mm]	706
Rolling circumference [mm].	4716
Tread depth (mm)	45,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	311.25
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 D	2650	65		1,60	
139 E	2430	70		1,60	