

## **TYRES**

Product group	Tyres
Item number	10626376
Valid tyre size	460 / 85 R 34
LI / SI / PR	147 D / 144 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85



## Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



## **Technical Informations**

Item number	10626376
EAN	3286340563611
Valid tyre size	460 / 85 R 34
Alternative size 1	18.4R34
LI / SI / PR	147 D / 144 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	130,60
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	1,60
Section width (mm)	487
Outer diameter of tyre [mm].	1652
Stat. radius (SLR) [mm]	745
Rolling circumference [mm].	4956
Tread depth (mm)	50,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	382.5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 D	3075	65		1,60	
144 E	2800	70		1,60	