

TYRES

Product group	Tyres	
Item number	10626523	
Valid tyre size	620 / 75 R 32	
LI / SI / PR	172 A8 / 172 B	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Maxi Traction Harvest	



Notes and features

- The Firestone Maxi Traction Harvest is a radial tractor tyre specially designed for harvesters.
- It offers excellent traction on the field.

- The shape of the lugs, which overlap in the center of the tread, the high number of lugs and the carcass construction ensure exceptional ride comfort on and off the road.
- The large contact area protects the soil and prevents heavy soil compaction.



Technical Informations

Item number	10626523
EAN	3286341703214
Valid tyre size	620 / 75 R 32
Alternative size 1	24.5R32
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction Harvest
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	249,53
Recommended rim size	DW20B
Permitted rim size	DW21B, DW23B
Maximum air pressure [bar].	3,20
Section width (mm)	630
Outer diameter of tyre [mm].	1760
Stat. radius (SLR) [mm]	794
Rolling circumference [mm].	5271
Tread depth (mm)	57,0
Tyre capacity 75% [ltr.]	650
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		3,20	
172 B	6300	50		3,20	