

TYRES

| Product group | Tyres |
|-----------------|---------------|
| Item number | 10626665 |
| Valid tyre size | 360 / 70 R 28 |
| LI / SI / PR | 125 D / 122 E |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Performer 70 |



Notes and features

- Unique double-angle lug technology.
- Large ground contact area due to stronger deflection and flatter tread pattern contour.
- Increased ride comfort.



Technical Informations

| Item number | 10626665 |
|------------------------------|---------------|
| EAN | 3286340341516 |
| Valid tyre size | 360 / 70 R 28 |
| LI / SI / PR | 125 D / 122 E |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Performer 70 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 65,80 |
| Recommended rim size | 11 |
| Permitted rim size | 10, 12 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 360 |
| Outer diameter of tyre [mm]. | 1256 |
| Stat. radius (SLR) [mm] | 562 |
| Rolling circumference [mm]. | 3768 |
| Tread depth (mm) | 39,5 |
| Number of lugs | 20x2 |
| Tyre capacity 75% [ltr.] | 147 |
| Guarantee period | 10 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 125 D | 1650 | 65 | | 1,60 | |
| 122 E | 1500 | 70 | | 1,60 | |