

TYRES

Product group	Tyres	
Item number	10627112	
Valid tyre size	480 / 65 R 24	
LI / SI / PR	133 D / 130 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Maxi Traction 65	



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



Technical Informations

Item number	10627112
EAN	3286340894913
Valid tyre size	480 / 65 R 24
LI / SI / PR	133 D / 130 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction 65
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	87,74
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	473
Outer diameter of tyre [mm].	1237
Stat. radius (SLR) [mm]	557
Rolling circumference [mm].	3702
Tread depth (mm)	44,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	218.25
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 D	2060	65		1,60	
130 E	1900	70		1,60	