Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10627202	
Valid tyre size	600 / 65 R 34	
LI / SI / PR	151 D / 148 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Maxi Traction 65	



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10627202
EAN	3286340897815
Valid tyre size	600 / 65 R 34
LI / SI / PR	151 D / 148 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction 65
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	170,03
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	590
Outer diameter of tyre [mm].	1639
Stat. radius (SLR) [mm]	737
Rolling circumference [mm].	4923
Tread depth (mm)	53,5
Number of lugs	20x2
Tyre capacity 75% [ltr.]	463.5
Guarantee period	10 years
E-Ready	No

12.03.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 D	3450	65		1,60	
148 E	3150	70		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.