# Bohnenkamp Moving Professionals

15.03.2025

### TYRES

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 10627301       |
| Valid tyre size | 230 / 95 R 32  |
| LI / SI / PR    | 143 A2 / 128 D |
| TL/TT           | TL             |
| Brand           | Firestone      |
| Tread pattern   | Performer 95   |



#### Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.

## Bohnenkamp Moving Professionals

### **Technical Informations**

| Item number                  | 10627301       |
|------------------------------|----------------|
| EAN                          | 3286340603119  |
| Valid tyre size              | 230 / 95 R 32  |
| LI / SI / PR                 | 143 A2 / 128 D |
| TL/TT                        | TL             |
| Brand                        | Firestone      |
| Tread pattern                | Performer 95   |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | not necessary  |
| Nettogewicht [kg] (gültig)   | 50,00          |
| Recommended rim size         | 8              |
| Permitted rim size           | 7              |
| Maximum air pressure [bar].  | 4,00           |
| Section width (mm)           | 220            |
| Outer diameter of tyre [mm]. | 1254           |
| Stat. radius (SLR) [mm]      | 592            |
| Rolling circumference [mm].  | 3861           |
| Tread depth (mm)             | 27,7           |
| Number of lugs               | 34x2           |
| Tyre capacity 75% [ltr.]     | 72.75          |
| Guarantee period             | 10 years       |
| E-Ready                      | No             |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 143 A2 | 2725               | 10           |               | 4,00                        |              |
| 128 D  | 1800               | 65           |               | 4,00                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.