

TYRES

Product group	Tyres
Item number	10627327
Valid tyre size	230 / 95 R 44
LI / SI / PR	148 A2 / 134 D
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 95



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.

Technical Informations

Item number	10627327
EAN	3286340603812
Valid tyre size	230 / 95 R 44
LI / SI / PR	148 A2 / 134 D
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 95
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	65,00
Recommended rim size	8
Permitted rim size	7
Maximum air pressure [bar].	4,00
Section width (mm)	233
Outer diameter of tyre [mm].	1558
Stat. radius (SLR) [mm]	737
Rolling circumference [mm].	4797
Tread depth (mm)	28,6
Number of lugs	40x2
Tyre capacity 75% [ltr.]	96
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A2	3150	10		4,00	
134 D	2120	65		4,00	