

TYRES

Product group	Tyres
Item number	10627332
Valid tyre size	300 / 95 R 46
LI / SI / PR	162 A2 / 148 D
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 95



Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



Technical Informations

Item number	10627332
EAN	3286340604017
Valid tyre size	300 / 95 R 46
LI / SI / PR	162 A2 / 148 D
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 95
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	115,00
Recommended rim size	10
Permitted rim size	9, 11
Maximum air pressure [bar].	4,00
Section width (mm)	313
Outer diameter of tyre [mm].	1737
Stat. radius (SLR) [mm]	822
Rolling circumference [mm].	5348
Tread depth (mm)	33,0
Number of lugs	34x2
Tyre capacity 75% [ltr.]	179.25
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A2	4750	10		4,00	
148 D	3150	65		4,00	