

TYRES

| | |
|-----------------|-------------------|
| Product group | Tyres |
| Item number | 10628150 |
| Valid tyre size | 500 / 70 R 24 |
| LI / SI / PR | 164 A8 / 164 B |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Duraforce Utility |



Notes and features

- For light industrial use.
 - Very good traction on hard surfaces.
 - Excellent stability.
- Even wear.
 - Cut and shock resistant.

Technical Informations

| | |
|------------------------------|-------------------|
| Item number | 10628150 |
| EAN | 3286340602914 |
| Valid tyre size | 500 / 70 R 24 |
| LI / SI / PR | 164 A8 / 164 B |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Duraforce Utility |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 133,50 |
| Recommended rim size | DW16L |
| Permitted rim size | DW15L |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 520 |
| Outer diameter of tyre [mm]. | 1329 |
| Stat. radius (SLR) [mm] | 598 |
| Rolling circumference [mm]. | 4012 |
| Tyre capacity 75% [ltr.] | 261 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 164 A8 | 5000 | 40 | | 4,00 | |
| 164 B | 5000 | 50 | | 4,00 | |