

TYRES

Product group	Tyres
Item number	10926387
Valid tyre size	1250 / 50 R 32
LI / SI / PR	188 A8 / 185 B
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10926387
EAN	8590341076496
Valid tyre size	1250 / 50 R 32
LI / SI / PR	188 A8 / 185 B
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	555,00
Recommended rim size	40
Permitted rim size	44
Maximum air pressure [bar].	2,40
Section width (mm)	1230
Outer diameter of tyre [mm].	2040
Stat. radius (SLR) [mm]	910
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6030
Tread depth (mm)	64,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
188 A8	10000	40		2,40	
185 B	9250	50		2,40	