

TYRES

Product group	Tyres
Item number	10926460
Valid tyre size	650 / 60 R 34
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10926460
EAN	8059971063783
Valid tyre size	650 / 60 R 34
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	215,60
Recommended rim size	20
Permitted rim size	21, 23
Maximum air pressure [bar].	2,40
Section width (mm)	650
Outer diameter of tyre [mm].	1638
Stat. radius (SLR) [mm]	740
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4935
Tread depth (mm)	56,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		2,40	
159 D	4375	65		2,40	