Bohnenkamp Moving Professionals

14.03.2025

TYRES

Product group	Tyres
Item number	10926480
Valid tyre size	270 / 80 R 32
LI / SI / PR	131 A8 / 128 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 90



Mitas

Notes and features

- The AC 90 is a modern row crop tyre for driving on row crops.
- The rounded lugs and lug shoulders effectively protect crops.
- The tyre is characterised by its excellent traction, high load capacity as well as excellent ride comfort at speeds up to 50 km/h.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10926480
EAN	8059971059199
Valid tyre size	270 / 80 R 32
LI / SI / PR	131 A8 / 128 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 90
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	45,00
Recommended rim size	9
Permitted rim size	W8, W10
Maximum air pressure [bar].	4,00
Section width (mm)	270
Outer diameter of tyre [mm].	1225
Stat. radius (SLR) [mm]	563
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3690
Tread depth (mm)	33,0
Number of lugs	21x2
Lug width (mm)	33
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 A8	1950	40		4,00	
128 B	1800	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.