Bohnenkamp Moving Professionals

14.03.2025

TYRES

| Product group | Tyres | |
|-----------------|------------------|--|
| Item number | 10926510 | |
| Valid tyre size | VF 480 / 95 R 50 | |
| LI / SI / PR | 170 B | |
| TL/TT | TL | |
| Brand | Mitas | |
| Tread pattern | HC 2000 | |



Mitas

Notes and features

- The Mitas HC 2000 is a VF tyre (Very High Flexion) for high-performance tractors.
- Due to its flexible casing, soil compaction is kept low and the soil is optimally protected despite its high load capacity.
- Thanks to the VF technology, the tyre offers up to 40% higher loading capacity at the same inflation pressure or the same loading capacity at an inflation pressure reduced by up to 40%.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 10926510 |
|------------------------------|------------------|
| EAN | 8590341081513 |
| Valid tyre size | VF 480 / 95 R 50 |
| LI / SI / PR | 170 B |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | HC 2000 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 238,00 |
| Recommended rim size | 16L |
| Permitted rim size | 15L, 18L |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 485 |
| Outer diameter of tyre [mm]. | 2150 |
| Stat. radius (SLR) [mm] | 970 |
| Speed Radius Index (SRI) | 1050 |
| Rolling circumference [mm]. | 6400 |
| Tread depth (mm) | 53,0 |
| Number of lugs | 28x2 |
| Tyre capacity 75% [ltr.] | 650 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 170 B | 6000 | 50 | | 1,60 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.