

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10926526 |
| Valid tyre size | 380 / 95 R 38 |
| LI / SI / PR | 150 A8 / 147 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 85 Row Crop |



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas AC 85 Row Crop is a row crop tyre.
- Its optimum lug height ensures very good traction and tracking as well as good self-cleaning properties.
- Thanks to the narrow tyre width, rounded lugs and tyre shoulders, crops and soil are optimally protected.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10926526 |
| EAN | 8590341077615 |
| Valid tyre size | 380 / 95 R 38 |
| LI / SI / PR | 150 A8 / 147 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 85 Row Crop |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 98,97 |
| Recommended rim size | W12 |
| Permitted rim size | W11, W13 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 380 |
| Outer diameter of tyre [mm]. | 1680 |
| Stat. radius (SLR) [mm] | 770 |
| Rolling circumference [mm]. | 5050 |
| Tread depth (mm) | 44,0 |
| Number of lugs | 24x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 150 A8 | 3350 | 40 | | 2,40 | |
| 147 D | 3075 | 65 | | 2,40 | |