

TYRES

Product group	Tyres	
Item number	10926536	
Valid tyre size	380 / 105 R 54	
LI / SI / PR	162 A8 / 164 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 85	



Mitas

Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.



Technical Informations

Item number	10926536
EAN	8590341090836
Valid tyre size	380 / 105 R 54
LI / SI / PR	162 A8 / 164 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	145,38
Recommended rim size	W10
Permitted rim size	W9, W11
Maximum air pressure [bar].	3,20
Section width (mm)	380
Outer diameter of tyre [mm].	2170
Stat. radius (SLR) [mm]	1012
Speed Radius Index (SRI)	1050
Rolling circumference [mm].	6580
Tread depth (mm)	42,0
Number of lugs	34x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		3,20	
164 D	5000	65		3,20	