

TYRES

Product group	Tyres
Item number	10927200
Valid tyre size	580 / 85 R 42
LI / SI / PR	166 A8 / 163 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10927200
EAN	8590341074874
Valid tyre size	580 / 85 R 42
LI / SI / PR	166 A8 / 163 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	236,00
Recommended rim size	18
Permitted rim size	20, 21
Maximum air pressure [bar].	1,60
Section width (mm)	567
Outer diameter of tyre [mm].	2045
Stat. radius (SLR) [mm]	920
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6100
Tread depth (mm)	58,0
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A8	5300	40		1,60	
163 D	4875	65		1,60	