

TYRES

Product group	Tyres
Item number	10927740
Valid tyre size	500 / 85 R 24
LI / SI / PR	158 A8 / 171 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10927740
EAN	8059971036985
Valid tyre size	500 / 85 R 24
LI / SI / PR	158 A8 / 171 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	133,30
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	2,80
Section width (mm)	528
Outer diameter of tyre [mm].	1458
Stat. radius (SLR) [mm]	621
Rolling circumference [mm].	4237
Tread depth (mm)	38,0
Number of lugs	20x2
Lug width (mm)	43
Tyre capacity 75% [ltr.]	310
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40	Drive Wheel	2,80	
171 A8	6150	40	Free Rolling	2,80	