

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 10927750       |
| Valid tyre size | 540 / 65 R 24  |
| LI / SI / PR    | 143 A8 / 140 D |
| TL/TT           | TL             |
| Brand           | Mitas          |
| Tread pattern   | AC 65          |



**Mitas**

## Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 10927750       |
| EAN                          | 8059971056907  |
| Valid tyre size              | 540 / 65 R 24  |
| LI / SI / PR                 | 143 A8 / 140 D |
| TL/TT                        | TL             |
| Brand                        | Mitas          |
| Tread pattern                | AC 65          |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | not necessary  |
| Nettogewicht [kg] (gültig)   | 99,40          |
| Recommended rim size         | 16             |
| Permitted rim size           | 18, 15         |
| Maximum air pressure [bar].  | 1,60           |
| Section width (mm)           | 523            |
| Outer diameter of tyre [mm]. | 1317           |
| Stat. radius (SLR) [mm]      | 590            |
| Speed Radius Index (SRI)     | 625            |
| Rolling circumference [mm].  | 3922           |
| Tread depth (mm)             | 45,0           |
| Number of lugs               | 19x2           |
| Lug width (mm)               | 41             |
| E-Ready                      | No             |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 143 A8 | 2725               | 40           |               | 1,60                     |              |
| 140 D  | 2500               | 65           |               | 1,60                     |              |