Bohnenkamp Moving Professionals

Product group	Tyres
Item number	10927805
Valid tyre size	440 / 70 R 28
LI / SI / PR	152 A8 / 152 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 G



Mitas

Notes and features

- The AC 70 G is a grassland wide-base tyre with optimal road characteristics.
- The big, wide lugs provide excellent soil protection.
- Its wide contact area ensures high ride comfort on the road.
- The wear-resistant rubber compound ensures a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10927805
EAN	8059971066623
Valid tyre size	440 / 70 R 28
LI / SI / PR	152 A8 / 152 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 G
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	95,90
Recommended rim size	13
Permitted rim size	14, 15
Maximum air pressure [bar].	3,20
Section width (mm)	435
Outer diameter of tyre [mm].	1348
Stat. radius (SLR) [mm]	604
Rolling circumference [mm].	4027
Tread depth (mm)	37,0
Number of lugs	19x2
Lug width (mm)	34
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		3,20	
152 B	3550	50		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.