

TYRES

Product group	Tyres
Item number	10927830
Valid tyre size	540 / 65 R 28
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65



Mitas

Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.



Technical Informations

Item number	10927830
EAN	8059971062830
Valid tyre size	540 / 65 R 28
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	111,30
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	1,60
Section width (mm)	530
Outer diameter of tyre [mm].	1410
Stat. radius (SLR) [mm]	624
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4145
Tread depth (mm)	45,0
Number of lugs	20x2
Lug width (mm)	39
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		1,60	
142 D	2650	65		1,60	