

TYRES

Product group	Tyres
Item number	10927855
Valid tyre size	600 / 70 R 28
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10927855
EAN	8059971061031
Valid tyre size	600 / 70 R 28
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	177,00
Recommended rim size	18
Permitted rim size	20
Maximum air pressure [bar].	2,40
Section width (mm)	627
Outer diameter of tyre [mm].	1574
Stat. radius (SLR) [mm]	696
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4660
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		2,40	
157 D	4125	65		2,40	