

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10927890 |
| Valid tyre size | 480 / 70 R 30 |
| LI / SI / PR | 141 A8 / 141 B |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 70 T |



Mitas

Notes and features

- The AC 70 T is a tractor tyre for heavy field work.
- Its high lugs provide excellent traction.
- Reduced slip thanks to its outstanding self-cleaning properties.
- The tyre is characterised by its versatility and can also be used in vineyards and orchards, for example.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10927890 |
| EAN | 8059971054699 |
| Valid tyre size | 480 / 70 R 30 |
| LI / SI / PR | 141 A8 / 141 B |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 70 T |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 108,40 |
| Recommended rim size | 15 |
| Permitted rim size | 14, 16 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 496 |
| Outer diameter of tyre [mm]. | 1477 |
| Stat. radius (SLR) [mm] | 667 |
| Speed Radius Index (SRI) | 700 |
| Rolling circumference [mm]. | 4435 |
| Tread depth (mm) | 52,0 |
| Number of lugs | 19x2 |
| Lug width (mm) | 38 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 141 A8 | 2575 | 40 | | 1,60 | |
| 141 B | 2575 | 50 | | 1,60 | |