

TYRES

Product group	Tyres
Item number	10927895
Valid tyre size	500 / 85 R 30
LI / SI / PR	164 A8 / 176 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10927895
EAN	8059971064292
Valid tyre size	500 / 85 R 30
LI / SI / PR	164 A8 / 176 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	156,40
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	2,80
Section width (mm)	517
Outer diameter of tyre [mm].	1605
Stat. radius (SLR) [mm]	680
Rolling circumference [mm].	4669
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40	Drive Wheel	2,80	
176 A8	7100	40	Free Rolling	2,80	