

## TYRES

Product group	Tyres
Item number	10927925
Valid tyre size	710 / 55 R 30
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp  
■ ■ ● Moving Professionals

**Mitas**

## Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

## Technical Informations

Item number	10927925
EAN	8059971065886
Valid tyre size	710 / 55 R 30
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	192,90
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	690
Outer diameter of tyre [mm].	1500
Stat. radius (SLR) [mm]	674
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4475
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		2,40	
159 D	4375	65		2,40	