

TYRES

Product group	Tyres
Item number	10927935
Valid tyre size	710 / 60 R 30
LI / SI / PR	165 A8 / 162 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10927935
EAN	8059971036572
Valid tyre size	710 / 60 R 30
LI / SI / PR	165 A8 / 162 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	216,80
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	708
Outer diameter of tyre [mm].	1646
Stat. radius (SLR) [mm]	730
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4870
Tread depth (mm)	59,0
Number of lugs	17x2
Lug width (mm)	55
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 A8	5150	40		2,40	
162 D	4750	65		2,40	