# Bohnenkamp Moving Professionals

14.03.2025

#### **TYRES**

Product group	Tyres
Item number	10927938
Valid tyre size	710 / 65 R 30
LI / SI / PR	182 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

#### Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10927938
EAN	8059971036954
Valid tyre size	710 / 65 R 30
LI / SI / PR	182 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	235,40
Recommended rim size	23
Permitted rim size	25
Maximum air pressure [bar].	2,40
Section width (mm)	708
Outer diameter of tyre [mm].	1698
Stat. radius (SLR) [mm]	730
Rolling circumference [mm].	4950
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
182 A8	8500	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.