Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	10927940
Valid tyre size	650 / 75 R 32
LI / SI / PR	167 A8 / 164 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 75 G



Mitas

Notes and features

- Wide-base tyre for grassland with optimal road characteristics.
- Economical due to low wear.

17.05.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10927940
EAN	8059971041828
Valid tyre size	650 / 75 R 32
LI / SI / PR	167 A8 / 164 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 75 G
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	211,60
Recommended rim size	DW20B
Permitted rim size	DW21B
Maximum air pressure [bar].	2,40
Section width (mm)	635
Outer diameter of tyre [mm].	1798
Stat. radius (SLR) [mm]	782
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5245
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		2,40	
164 B	5000	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.