

TYRES

Product group	Tyres	
Item number	10927942	
Valid tyre size	IF 650 / 75 R 32 CFO	
LI / SI / PR	176 A8	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 75 G	



Mitas

Notes and features

 Wide-base tyre for grassland with optimal road characteristics. • Economical due to low wear.



Technical Informations

	40007040
Item number	10927942
EAN	8059971065800
Valid tyre size	IF 650 / 75 R 32 CFO
LI / SI / PR	176 A8
TL/TT	TL
Brand	Mitas
Tread pattern	AC 75 G
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	232,20
Recommended rim size	23
Permitted rim size	20, 21
Maximum air pressure [bar].	2,80
Section width (mm)	660
Outer diameter of tyre [mm].	1770
Stat. radius (SLR) [mm]	782
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5245
Tread depth (mm)	46,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.