Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10927950	
Valid tyre size	650 / 75 R 32	
LI / SI / PR	172 A8 / 169 B	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 70 G	



Mitas

Notes and features

- The AC 70 G is a grassland wide-base tyre with optimal road characteristics.
- The big, wide lugs provide excellent soil protection.
- Its wide contact area ensures high ride comfort on the road.
- The wear-resistant rubber compound ensures a long service life.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10927950
EAN	8059971060522
Valid tyre size	650 / 75 R 32
LI / SI / PR	172 A8 / 169 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 G
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	222,80
Recommended rim size	20
Permitted rim size	21
Maximum air pressure [bar].	3,20
Section width (mm)	650
Outer diameter of tyre [mm].	1795
Stat. radius (SLR) [mm]	790
Rolling circumference [mm].	5255
Tread depth (mm)	46,0
Lug width (mm)	50
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		3,20	
169 B	5800	50		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.