

## **TYRES**

Product group	Tyres	
Item number	10927980	
Valid tyre size	900 / 60 R 32	
LI / SI / PR	176 A8 / 173 B	
TL/TT	TL	
Brand	Mitas	
Tread pattern	SFT	



Mitas

## Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.



## **Technical Informations**

Item number	10927980
EAN	8059971063677
Valid tyre size	900 / 60 R 32
LI / SI / PR	176 A8 / 173 B
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	330,40
Recommended rim size	27
Permitted rim size	30
Maximum air pressure [bar].	2,40
Section width (mm)	857
Outer diameter of tyre [mm].	1905
Stat. radius (SLR) [mm]	850
Speed Radius Index (SRI)	900
Rolling circumference [mm].	5700
Tread depth (mm)	56,0
Number of lugs	22x2
Lug width (mm)	58
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,40	
173 B	6500	50		2,40	