

TYRES

Product group	Tyres
Item number	10927982
Valid tyre size	1050 / 50 R 32
LI / SI / PR	178 A8 / 178 B
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10927982
EAN	8059971039689
Valid tyre size	1050 / 50 R 32
LI / SI / PR	178 A8 / 178 B
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	458,40
Recommended rim size	36
Maximum air pressure [bar].	2,40
Section width (mm)	1015
Outer diameter of tyre [mm].	1890
Stat. radius (SLR) [mm]	845
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5640
Tyre capacity 75% [ltr.]	875
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40		2,40	
178 B	7500	50		2,40	