

TYRES

Product group	Tyres	
Item number	10928025	
Valid tyre size	460 / 85 R 34	
LI / SI / PR	147 A8 / 147 B	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 85	



Mitas

Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.



Technical Informations

Item number	10928025
EAN	8059971040197
Valid tyre size	460 / 85 R 34
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	129,10
Recommended rim size	16
Permitted rim size	15, 14
Maximum air pressure [bar].	1,60
Section width (mm)	518
Outer diameter of tyre [mm].	1676
Stat. radius (SLR) [mm]	756
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4982
Tread depth (mm)	51,0
Lug width (mm)	48
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		1,60	
147 B	3075	50		1,60	