

TYRES

Product group	Tyres
Item number	10928060
Valid tyre size	900 / 70 R 32
LI / SI / PR	188 A8 / 185 B
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

## Technical Informations

Item number	10928060
EAN	8059971061048
Valid tyre size	900 / 70 R 32
LI / SI / PR	188 A8 / 185 B
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	449,20
Recommended rim size	27
Permitted rim size	30
Maximum air pressure [bar].	3,20
Section width (mm)	895
Outer diameter of tyre [mm].	2050
Stat. radius (SLR) [mm]	896
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6050
Tread depth (mm)	64,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
188 A8	10000	40		3,20	
185 B	9250	50		3,20	