# Bohnenkamp Moving Professionals

21.05.2025

### **TYRES**

Product group	Tyres
Item number	10928080
Valid tyre size	13.6 R 36
LI / SI / PR	127 A8 / 124 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 90



Mitas

#### Notes and features

- The AC 90 is a modern row crop tyre for driving on row crops.
- The rounded lugs and lug shoulders effectively protect crops.
- The tyre is characterised by its excellent traction, high load capacity as well as excellent ride comfort at speeds up to 50 km/h.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10928080
EAN	8059971059397
Valid tyre size	13.6 R 36
LI / SI / PR	127 A8 / 124 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 90
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	72,50
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	1,60
Section width (mm)	360
Outer diameter of tyre [mm].	1499
Stat. radius (SLR) [mm]	692
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4492
Tread depth (mm)	38,0
Lug width (mm)	39
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A8	1750	40		1,60	
124 B	1600	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.