

TYRES

Product group	Tyres
Item number	10928090
Valid tyre size	650 / 85 R 38
LI / SI / PR	176 A8 / 173 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
 - Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10928090
EAN	8059971036596
Valid tyre size	650 / 85 R 38
LI / SI / PR	176 A8 / 173 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	329,60
Recommended rim size	23
Permitted rim size	20, 21
Maximum air pressure [bar].	2,40
Section width (mm)	720
Outer diameter of tyre [mm].	2070
Stat. radius (SLR) [mm]	920
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6130
Tread depth (mm)	63,0
Number of lugs	21x2
Lug width (mm)	60
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		2,40	
173 D	6500	65		2,40	