

TYRES

Product group	Tyres	
Item number	10928145	
Valid tyre size	710 / 70 R 38	
LI / SI / PR	169 A8 / 166 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	SFT	



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.



Technical Informations

Item number	10928145
EAN	8059971068474
Valid tyre size	710 / 70 R 38
LI / SI / PR	169 A8 / 166 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	293,90
Recommended rim size	23
Maximum air pressure [bar].	1,60
Section width (mm)	736
Outer diameter of tyre [mm].	1958
Stat. radius (SLR) [mm]	870
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5780
Tread depth (mm)	63,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A8	5800	40		1,60	
166 D	5300	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.