

TYRES

Product group	Tyres
Item number	10928195
Valid tyre size	650 / 65 R 38
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10928195
EAN	8059971040586
Valid tyre size	650 / 65 R 38
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	214,40
Recommended rim size	W18L
Permitted rim size	DW20B, DW21B
Maximum air pressure [bar].	1,60
Section width (mm)	645
Outer diameter of tyre [mm].	1828
Stat. radius (SLR) [mm]	810
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5445
Tread depth (mm)	57,0
Number of lugs	20x2
Lug width (mm)	59
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		1,60	
157 D	4125	65		1,60	