

TYRES

Product group	Tyres	
Item number	10928237	
Valid tyre size	VF 650 / 65 R 42	
LI / SI / PR	170 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	HC 2000	



Mitas

Notes and features

- The Mitas HC 2000 is a VF tyre (Very High Flexion) for high-performance tractors.
- Due to its flexible casing, soil compaction is kept low and the soil is optimally protected despite its high load capacity.
- Thanks to the VF technology, the tyre offers up to 40% higher loading capacity at the same inflation pressure or the same loading capacity at an inflation pressure reduced by up to 40%.



Technical Informations

Item number	10928237
EAN	8059971043167
Valid tyre size	VF 650 / 65 R 42
LI / SI / PR	170 D
TL/TT	TL
Brand	Mitas
Tread pattern	HC 2000
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	256,40
Recommended rim size	23B
Permitted rim size	21B
Maximum air pressure [bar].	1,60
Section width (mm)	671
Outer diameter of tyre [mm].	1910
Stat. radius (SLR) [mm]	860
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5740
Tread depth (mm)	51,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 D	6000	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.