# Bohnenkamp Moving Professionals

12.03.2025

#### **TYRES**

Product group	Tyres
Item number	10928263
Valid tyre size	680 / 80 R 42
LI / SI / PR	183 A8 / 180 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

#### Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10928263
EAN	8059971066791
Valid tyre size	680 / 80 R 42
LI / SI / PR	183 A8 / 180 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	382,70
Recommended rim size	DW21B
Permitted rim size	DW20B, DW23B
Maximum air pressure [bar].	3,20
Section width (mm)	660
Outer diameter of tyre [mm].	2160
Stat. radius (SLR) [mm]	965
Speed Radius Index (SRI)	1025
Rolling circumference [mm].	6400
Tread depth (mm)	61,0
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
183 A8	8750	40		3,20	
180 D	8000	65		3,20	

12.03.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.