Bohnenkamp Moving Professionals

12.03.2025

TYRES

Product group	Tyres	
Item number	10928265	
Valid tyre size	480 / 80 R 46	
LI / SI / PR	158 A8 / 158 B	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AC 85	



Mitas

Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10928265
EAN	8059971036268
Valid tyre size	480 / 80 R 46
Alternative size 1	18.4R46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	181,10
Recommended rim size	16
Permitted rim size	14, 15
Maximum air pressure [bar].	2,40
Section width (mm)	507
Outer diameter of tyre [mm].	1960
Stat. radius (SLR) [mm]	896
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5886
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		2,40	
158 B	4250	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.