

TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 12426134       |
| Valid tyre size | 380 / 70 R 24  |
| LI / SI / PR    | 125 A8 / 125 B |
| TL/TT           | TL             |
| Brand           | Kleber         |
| Tread pattern   | Fitker         |



Notes and features

- Maximum traction due to optimised lug shape.
  - Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
  - Long service life.

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 12426134       |
| EAN                          | 3528707619815  |
| Valid tyre size              | 380 / 70 R 24  |
| LI / SI / PR                 | 125 A8 / 125 B |
| TL/TT                        | TL             |
| Brand                        | Kleber         |
| Tread pattern                | Fitker         |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | not necessary  |
| Nettogewicht [kg] (gültig)   | 62,00          |
| Recommended rim size         | 12             |
| Permitted rim size           | 11, 13         |
| Maximum air pressure [bar].  | 1,60           |
| Section width (mm)           | 390            |
| Outer diameter of tyre [mm]. | 1204           |
| Stat. radius (SLR) [mm]      | 536            |
| Rolling circumference [mm].  | 3569           |
| Tread depth (mm)             | 41,0           |
| Number of lugs               | 19x2           |
| Lug width (mm)               | 33             |
| Tyre capacity 75% [ltr.]     | 160            |
| E-Ready                      | No             |

Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 125 A8 | 1650               | 40           |               | 1,60                     |              |
| 125 B  | 1650               | 50           |               | 1,60                     |              |