

TYRES

Product group	Tyres
Item number	12426250
Valid tyre size	280 / 85 R 28
LI / SI / PR	118 A8 / 115 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker





Notes and features

- Very good traction through high tread lugs.
- Good self-cleaning.

• Even pressure distribution due to flat tread pattern.



Technical Informations

Item number	12426250
EAN	3528701618852
Valid tyre size	280 / 85 R 28
Alternative size 1	11.2R28
LI / SI / PR	118 A8 / 115 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	46,00
Recommended rim size	10
Permitted rim size	9
Maximum air pressure [bar].	1,60
Section width (mm)	297
Outer diameter of tyre [mm].	1200
Stat. radius (SLR) [mm]	543
Rolling circumference [mm].	3571
Tread depth (mm)	39,0
Number of lugs	19x2
Lug width (mm)	32
Tyre capacity 75% [ltr.]	100
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
118 A8	1320	40		1,60	
115 B	1215	50		1,60	