# Bohnenkamp Moving Professionals

### **TYRES**

Product group	Tyres
Item number	12426265
Valid tyre size	320 / 85 R 28
LI / SI / PR	124 A8 / 121 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker



### Notes and features

- Very good traction through high tread lugs. .
- Good self-cleaning.

• Even pressure distribution due to flat tread pattern.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	12426265
EAN	3528701617725
Valid tyre size	320 / 85 R 28
Alternative size 1	12.4R28
LI / SI / PR	124 A8 / 121 B
TL/TT	т
Brand	Kleber
Tread pattern	Traker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	59,00
Recommended rim size	11
Permitted rim size	10
Maximum air pressure [bar].	1,60
Section width (mm)	322
Outer diameter of tyre [mm].	1253
Stat. radius (SLR) [mm]	562
Rolling circumference [mm].	3721
Tread depth (mm)	42,0
Number of lugs	20x2
Lug width (mm)	35
Tyre capacity 75% [ltr.]	134
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 A8	1600	40		1,60	
121 B	1450	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.